

## S6800 Series



Bearing NO.	Shape Dimension(mm)								Basic Load Rating(N)		Weight (kg)
	d(mm)	d(inch)	D(mm)	D(inch)	B(mm)	B(inch)	r min(mm)	r min(inch)	Dynamic( Cr)	Static( Cor)	
S6800	10	0.3937	19	0.7480	5	0.1969	0.3	0.0118	1590	750	0.0050
S6801	12	0.4724	21	0.8268	5	0.1969	0.3	0.0118	1910	1040	0.0060
S6802	15	0.5906	24	0.9449	5	0.1969	0.3	0.0118	2070	1250	0.0070
S6803	17	0.6693	26	1.0236	5	0.1969	0.3	0.0118	2130	1360	0.0080
S6804	20	0.7874	32	1.2598	7	0.2756	0.3	0.0118	3480	2230	0.0190
S6805	25	0.9843	37	1.4567	7	0.2756	0.3	0.0118	3680	2630	0.0220
S6806	30	1.1811	42	1.6535	7	0.2756	0.3	0.0118	4000	3150	0.0260
S6807	35	1.3780	47	1.8504	7	0.2756	0.3	0.0118	4270	3600	0.0290
S6808	40	1.5748	52	2.0472	7	0.2756	0.3	0.0118	4410	3890	0.0330
S6809	45	1.7717	58	2.2835	7	0.2756	0.3	0.0118	4590	4330	0.0400
S6810	50	1.9685	65	2.5591	7	0.2756	0.3	0.0118	6610	6080	0.0520